

SOUND MONITOR: QUICK START GUIDE



**HIGH-QUALITY, ACCURATE
SOUND LEVEL MEASUREMENTS**
CLASS ONE PERFORMANCE



5 LED STATUS LIGHTS
Clear status display through
sequence and color.



SIMPLE INSTALLATION
Simple strap or bolt to pole,
or secure on tripod.



ROBUST DESIGN
IP65-rated



**COMPACT &
LIGHTWEIGHT**



GLOBAL COMMUNICATION
WiFi, 4G/LTE, PoE



**UNIQUE
OMNIDIRECTIONAL
MICROPHONE DESIGN**



**AUTOMATED
FIELD CALIBRATION**

Automatically corrects and documents
the output with field calibrator.

**WIDE RANGE
POWER INPUT**
From 5V to 57V


**WATERPROOF
POWER CONNECTOR**
Mains Electricity
SWARM Battery
Solar panel
PoE



**WEATHERPROOF
MICROPHONE DESIGN**



DUST MONITOR: SETUP



Mount the Monitor

Firmly to the supplied tripod, and position securely.

Power the Monitor

Connect the power cable to the Monitor. Plug in power to the mains: 15 - 40V DC @1.5A max or battery pack

Create an Account

Follow the steps below to create your account, validate your email and login to the monitoring live data feed.

Monitor and Check

Login anytime to the monitoring platform to track your data and access live graphical reporting.

1. Visit <https://honeycomb.omnidots.com/>

2. Scroll down and click

Register and take a look

3. Fill in fields and click

Sign up


4. Check your inbox for the Validation Email and click



Confirm e-mail address

I have read and agree to the terms and conditions

5. Read and agree to the Terms and Conditions:

6. You are now logged in and able to view your sound monitor data - click [View data](#) button to access live data feed.

 **Control Hire**

Name ^	Status ^	Device ^	Last contact ^	Battery charge ^	Options
CH807	● online		6 minutes ago	80%  6 minutes ago	View data

7. Data will automatically populate for your monitor and display – click “to now”:

