

FIRESAFE™

BUSHFIRE RATED ROLLER SHUTTER

BUSHFIRE RATED



TESTED BY CSIRO

BUSHFIRE RATED TO BAL A40

MEETS AUS BUSHFIRE STANDARDS

PROTECT YOUR HOME! PROTECT YOUR FAMILY!



FIRESAFE™ ROLLER SHUTTERS

As more Australians move to country and semi-rural areas for a better lifestyle, and our urban sprawl takes homeowners closer to bushfire prone areas, protection from bushfires has become increasingly important in Australia.

It is for this reason that CW Products, (Australia's leading supplier of roller shutters and home automation products) has developed the **FireSafe™ Bushfire Rated Roller Shutter**.

FireSafe™ is bushfire rated to Bushfire Attack Level (BAL) A40 and is compliant with Australian Bushfire Construction Standard AS3959-2018 (Clauses 3.7 & 8.5.1).

At CW Products we're committed to helping protect Australian families and their homes!



FIRESAFE™ BENEFITS

- Bushfire rated to Bushfire Attack Level (BAL) A40.
- Tested by CSIRO (Report# FSZ1379).
- Complies with Australian Bushfire Construction Standard AS3959-2018 (Clauses 3.7 & 8.5.1).
- Radiant heat shielding properties to 40 kW/m².
- Commercial grade double wall extruded shutter profile for heavy duty strength and extreme heat protection.
- Heavy duty 68mm guide system for extra strength.
- Heavy duty steel axle and internal sealed bearings.
- Roll-tight design.
- Suitable for widespan widths up to 5800mm.
- High quality powder coated finish.
- Choice of profile colours.
- Either manual or motorised operation.
- FireSafe™ Authentication Plate fitted.
- Made in Australia.

CONTROL OPTIONS



Steel Cable Winder (Up To 50Kg)*



Spring Loaded With Key Lock



Crank Handle With Gear Ace (Up To 30Kg)



PowerSmart™ Control System With 12V Motor (Up To 50Kg)*†



Wall Switch With 240V Electric Manual Override Motor*



Remote Control With 240V Electric SIMU Hz Manual Override Motor



Crank Handle With 240V Electric Manual Override Motor

† When used in conjunction with an assist spring as per CW Products specifications.

* Control options must be installed in an indoor environment.

PROFILE COLOUR OPTIONS

Select from our wide range of high quality 36mm Extruded roller shutter profile colours.

	Cream		Black
	Magnolia Cream		Monument
	Clear Beige		Anodised Silver*
	White		Woodland Grey
	Shale Grey		

* Not available for pelmets & side frames. Powder coated options available.

TECHNICAL SPECIFICATIONS

Bushfire Attack Level Rating	BAL A40
Maximum Shutter Width	5800mm
Maximum Shutter Height	3000mm
Profile Slat Covering	36mm
Profile Slat Thickness	9.7mm
Axle Types	Octagonal Steel
Bottom Bar Dimensions	55mm x 8.5mm
Guide Dimensions	68mm x 25mm/14mm (Heavy Duty Guide)
Paint Finish	High Quality Powder Coat

For more information on FireSafe™ Roller Shutters, please contact your nearest dealer, installer or visit www.cwproducts.com.au!

Authorised Dealer:



BUSHFIRE
RATED
ROLLER
SHUTTERS



Exclusively distributed in Australia by **CW Products** Tel: +61 8 8341 0120 Web: www.cwproducts.com.au

Illustrations, photos and colours shown in this brochure are for illustrative purposes only. All technical specifications and dimensions are correct at time of printing and may change without notice. For more information please contact your CW Products representative. FireSafe and the FireSafe logo are trademarks of CW Products. © 2023 CW Products.