

CW RADIO REMOTE CONTROLS





Radio Remote Control Motorisation For Roller Shutters & Awnings



CW Products supplies some of the world's highest quality automation products and has created a high quality, value for money and versatile CW Motor & Accessories product range, that delivers affordability and allows you to be competitive in the marketplace.

The CW Radio Remote Controls range is compatible with most home automation systems, provides reliable, high performance and is suitable for operating a wide range of roller shutter, awning and screen applications.

MOBILE TRANSMITTERS

Description	Product Code		Technical Specifications	
CW Products Mobile Transmitter (Including Cradle)	41-400-501	 1 Channel	Wireless Switch	Class III
	41-400-505	 5 Channel	Protection Index	IP 30
	41-400-508	 8 Channel + Timer	Radio Frequency	433.92 MHz
	41-400-515	 15 Channel	Ambient Temperature Of Use	From 0°C to +60°C
			Range <small>Depending on environment & radio pollution</small>	- 200m in free field - 20m between two reinforced concrete walls
			Power Supply	3V lithium battery (CR 2430) Lifetime of approx 3 years (4 presses of 1sec/day)
			Dimensions	130mm x 45mm x 12mm



KEY RING TRANSMITTER

Description	Product Code		Technical Specifications	
CW Products Key Ring Transmitter	41-400-337	 1 Channel	Wireless Switch	Class III
			Protection Index	IP 30
			Radio Frequency	433.92 MHz
			Ambient Temperature Of Use	From -20°C to +70°C
			Range <small>Depending on environment & radio pollution</small>	- 30m in free field
			Power Supply	12V battery (27A)
			Dimensions	66mm x 34mm x 14mm

WALL TRANSMITTERS

Description	Product Code		Technical Specifications	
CW Products Wall Transmitter	41-400-401	 1 Channel	Wireless Switch	Class III
	41-400-405	 5 Channel	Wireless Switch	Class III
			Protection Index	IP 30
			Radio Frequency	433.92 MHz
			Ambient Temperature Of Use	From 0°C to +60°C
			Range <small>Depending on environment & radio pollution</small>	- 200m in free field - 20m between two reinforced concrete walls
			Power Supply	3V lithium battery (CR 2032) Lifetime of approx 3 years (4 presses of 1sec/day)
			Dimensions	80mm x 80mm x 14mm

EXTERNAL RECEIVERS

Description	Product Code		Technical Specifications	
CW Products Inline Receiver With 1000mm Cable To Motor	41-400-005		Power Supply	240 Volts - 50 Hz
			Protection Index	IP 44
CW Products Inline Receiver With 120mm Cable To Motor	41-400-006		Radio Frequency	433.92 MHz
			Ambient Temperature Of Use	From -30°C to +80°C
			Range <small>Depending on environment & radio pollution</small>	- 200m in free field - 20m between two reinforced concrete walls
			Compatibility	CW transmitter range
			Dimensions	120mm x 28mm x 25mm